

# PASS-THRU REFRIGERATOR

## Model: 2RE-PT

### 2-Section Extra-Wide Pass-Thru Refrigerator

2RE-PT - Stainless steel front, aluminum end panels and interior  
 2RE-SA-PT - Stainless steel exterior, aluminum interior  
 2RE-SS-PT - Stainless steel exterior and interior  
**Designed to maintain NSF-7 temperatures in 100°F ambient.**



#### Options and Accessories

(upcharge and lead times may apply)

|                                       |   |
|---------------------------------------|---|
| Stainless steel case back             | Custom laminates                          |
| Additional epoxy-coated steel shelves | Half doors                                |
| Chrome or stainless steel shelves     | Shallow depth                             |
| Pan slide assemblies                  | Hinged glass doors                        |
| Heavy-duty pilaster strips            | Increased refrigeration systems           |
| Rehinging of doors (consult factory)  | Special electrical req. (consult factory) |
| Expansion valve system                | <b>Correctional Facility Options</b>      |
| Wine display                          | • One way security screws                 |
| Adjustable legs                       | • Locking hasp (lock not included)        |
| Digital thermometer                   | • Stainless steel mesh cover              |
| Remote models                         | • Coverless hinges                        |

Consult factory for other model configurations, options and accessories.

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
 Phone: 215-244-1400  
 Fax: 215-244-9579

539 Dunksferry Road  
 Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

#### Standard Model Features

##### REFRIGERATION SYSTEM

Environmentally-safe R-134a refrigerant

Self contained, performance-rated refrigeration system

Automatic, electric condensate evaporator

##### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap-in door gaskets

Cylinder lock in door

Heavy-duty, epoxy-coated steel shelves

5" casters

##### MODEL FEATURES

LED interior lighting

External dial thermometer

Energy saving switch for door heaters

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

|  |                  |
|--|------------------|
| Net Capacity (cu. ft.)                   | 50 (1416 cu l)   |
| Width, Overall (in.)                     | 57 (1448 mm)     |
| Depth, Overall (in.) (incl. handles)     | 38 3/4 (984 mm)  |
| Depth [less doors] (in.)                 | 32 (813 mm)      |
| Depth [doors open 90°] (in.)             | 84 (2134 mm)     |
| Clear Door Width (in.)                   | 21 7/8 (556 mm)  |
| Clear Door Height (in.)                  | 58 5/8 (1489 mm) |
| Height, Overall (in.) (incl. 5" casters) | 82 1/4 (2089 mm) |
| No. of Doors                             | 4                |
| No. of Shelves                           | 6                |
| Shelf Area (sq. ft.)                     | 40.8 (3.8 sq m)  |
| Tray Slide Capacity (per section)        | 24               |

### REFRIGERANT DATA

|                             |      |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/3  |
| Capacity (BTU/Hr)*          | 2560 |

### ELECTRICAL DATA

|                                     |                     |
|-------------------------------------|---------------------|
| Voltage (int'l)                     | 115/60/1 (220/50/1) |
| Feed Wires (incl. ground)           | 3                   |
| Total Amps (int'l)                  | 7.2 (5.6)           |
| 10 ft. Cord/Plug [attached] (int'l) | Yes (No)            |

### SHIPPING DATA

|                              |                  |
|------------------------------|------------------|
| Height - Crated (in.)        | 85 1/2 (2172 mm) |
| Width - Crated (in.)         | 64 (1626 mm)     |
| Depth - Crated (in.)         | 42 (1067 mm)     |
| Volume - Crated (cu. ft.)    | 133 (3766 cu l)  |
| Weight Std - Crated (lbs.)   | 620 (281 kg)     |
| Weight SS - Crated (lbs.)    | 690 (313 kg)     |
| Weight Std - Uncrated (lbs.) | 450 (204 kg)     |
| Weight SS - Uncrated (lbs.)  | 530 (240 kg)     |


\* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.




Equipped with one NEMA-5-15P Plug  
(varies by country)

## Model Plan Views



FRONT VIEW



SIDE VIEW

**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required.

**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunkserry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



MADE IN THE U.S.A.

© Copyright 2015. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.